

4 3 2 1

PART NO. SEE TABLE

REVISIONS		LTR	DESCRIPTION	Drawing	DATE

Top view dimensions: 38.94, 19.47, 0.45, 8.10, 7.30, 2.30, 1.43, 0.50, 7.62, 3.17, 12.07, 2.00, 9.25, 0.120.

Side view dimensions: 1.97, 2.41, 2.25, 1.70, 41.13, 1.15±0.05, 4.00±0.05, 6.67, 5.05, 0.60.

RECOMMENDED P.C. B LAYOUT THICKNESS=1.0mm

Dimensions: 48.60, 38.94, 7.62, 0.60, 8.25, 1.905, 1.27, 1.70, 35.45, 38.94, 42.95, 45.15, 1.90.

Dimensions: 33.39, 0.84, 1.27, 1.905, 8.255, 7.62, 4.40, 3.90, 17.78, 35.46, 42.00, 42.53, 44.93, 1.27.

SECTION A-A

Dimensions: 1.23, 4.90, 0.70.

NOTE:

- MATERIAL:
HOUSING:HIGH TEMPERATURE THERMOPLASTIC,UL94V-0
COVER:HIGH TEMPERATURE THERMOPLASTIC,UL94V-0
TERMINAL:COPPER ALLOY,THICKNESS = 0.25 mm
FORLOCK:COPPER ALLOY,THICKNESS = 0.30 mm
- PLATING:
CONTACT:GOLD OVER 50u" MIN NICKEL UNDERPLATE
SOLDER TAIL:75u"MIN TIN 50u" MIN NICKEL UNDERPLATE
GOLD SPECIFICATION:SEE TABLE,
- ELECTRONICAL SPECIFICATION:
CURRENT RATING:1.5 AMPERE PER CONTACT
CONTACT RESISTANCE:30 MILLIOHMS MAX.
INSULATION RESISTANCE:1000 MEGOHMS MIN.
DIELECTRIC WITHSTANDING VOLTAGE:500 VDC.
OPERATING TEMPERATURE:-40C~+85C

Dimensions: 49.70, 20.00, 5.00, 2.40.

SECTION B-B

DIMENSION ARE MILLIMETERS TOLERANCES ARE : DECIMALS
.X i0 0.30
.XX i0 0.25
ANGLE:
X ± 3°

APPROVALS		DATE
DRAWN	GARY	12/03/08
CHECKED		
APPROVALS		

EVERTRON			
TITLE: SATA 22P 公頭沉板式			
SIZE	SCALE :	DRAWING NO.	REV.
mm	1 : 1	ET-SATA-22-L-XXX	AO
ID NO.	XXXXXXXXXX	SHEET 1 OF 1	

NO	DESCRIPTION	QTY	UNIT	DO NOT SCALE DRAWING

4 3 2 1